AMENDMENTS TO THE CLAIMS

1. (Original) A method of adapting a downhole multi-phase twin screw pump for

use in wells having a high gas content, comprising the steps of:

positioning a supplementary liquid channel in a housing of the pump in fluid

communication with a pumping screw; and

feeding supplementary liquid through the supplementary liquid channel to the

pumping screw, thereby enhancing a liquid seal around the pumping screw.

2. (Original) The method as defined in Claim 1, wherein the supplementary liquids

are provided by a liquid trap which captures a portion of a liquid stream being moved by the

pumping screw and recirculates that portion of the liquid stream as the supplementary liquid to

the supplementary liquid channel.

3. (Original) The method as defined in Claim 2, wherein the liquid trap is

positioned along a fluid flow passage extending through the housing of the pump.

4. (Original) The method as defined in Claim 2, wherein the liquid trap is

positioned adjacent a well head of the well.

5. (Currently amended) The method as defined in Claim 3-or-4, wherein the liquid trap

uses an educator to capture the portion of the liquid stream.

6. (Original) A method of adapting a downhole multi-phase twin screw pump for use

-2-

in wells having a high gas content, comprising the steps of:

positioning a supplementary liquid channel in a housing of the pump in fluid

communication with a pumping screw near an intake end of the pump;

providing a liquid trap which uses an educator to capture a portion of a liquid

stream being moved by the pumping screw;

and

LAW OFFICES OF CHRISTENSEN O'CONNOR JOHNSON KINDNESS^{PLLC} 1420 Fifth Avenue

Suite 2800 Seattle, Washington 98101

206.682.8100

feeding supplementary liquid from the liquid trap through the supplementary liquid channel to the pumping screw, thereby enhancing a liquid seal around the pumping screw.

7. (Original) The method as defined in Claim 6, wherein the liquid trap is positioned along a fluid flow passage extending through the housing of the pump.

8. (Original) The method as defined in Claim 6, wherein the liquid trap is positioned adjacent a well head of the well.

9. (Original) A downhole multi-phase twin screw pump, comprising:

a housing having an intake end, an output end, and a fluid flow passage that extends between the intake end and the output end;

twin pumping screws disposed in the fluid flow passage;

a supplementary liquid channel extending through the housing in fluid communication with at least one of the twin pumping screws near the intake end of the housing; and

means for feeding supplementary liquid through the supplementary liquid channel to the at least one of the twin pumping screw, thereby enhancing a liquid seal around the twin pumping screws.

10. (Original) The pump as defined in Claim 9, wherein the means for feeding supplementary liquid through the supplementary liquid channel is a liquid trap in communication with the fluid flow passage which captures a portion of a liquid stream being moved along the fluid flow passage by the twin pumping screws and recirculates that portion of the liquid stream as the supplementary liquid to the supplementary liquid channel.

11. (Original) The pump as defined in Claim 9, wherein the liquid trap uses an educator to capture the portion of the liquid stream.

12. (Original) A downhole multi-phase twin screw pump, comprising:

a housing having an intake end, an output end, and a fluid flow passage that extends between the intake end and the output end;

twin pumping screws disposed in the fluid flow passage;

a supplementary liquid channel extending through the housing in fluid

communication with at least one of the twin pumping screws near the intake end of the housing;

and

a liquid trap in communication with the fluid flow passage which uses an educator

to capture a portion of a liquid stream being moved along the fluid flow passage by the twin

pumping screws and feeds that portion of the liquid stream as supplementary liquid through the

supplementary liquid channel to the at least one of the twin pumping screw, thereby enhancing a

liquid seal around the twin pumping screws.

A downhole multi-phase twin screw pump, comprising in 13. (Original)

combination:

a housing having an intake end, an output end, and a fluid flow passage that

extends between the intake end and the output end;

twin pumping screws disposed in the fluid flow passage;

a supplementary liquid channel extending through the housing in fluid

communication with at least one of the twin pumping screws near the intake end of the housing;

and

a liquid trap positioned adjacent a well head of the well which uses an educator to

capture a portion of a liquid stream being moved through the well by the twin pumping screws

and feeds that portion of the liquid stream as supplementary liquid through the supplementary

liquid channel to the at least one of the twin pumping screw, thereby enhancing a liquid seal

around the twin pumping screws.

LAW OFFICES OF CHRISTENSEN O'CONNOR JOHNSON KINDNESSPLLC 1420 Fifth Avenue

Suite 2800 Seattle, Washington 98101 206.682.8100

-4-

(New) The method as defined in Claim 4, wherein the liquid trap uses an 14. educator to capture the portion of the liquid stream.